

モーター負荷テストデータ

モーター	プロペラ	ESC	電圧 (V)	スロットル 開度 (%)	電流 (A)	消費電力 (W)	推力 (g)	回転数 (r.p.m.)	効率 (g/W)	表面温度 (°C)
OMM-4715-400	OPM-1162-053	OCM-3035	22.2	50	5.6	124	1,100	4,200	8.7	34
				65	9.5	211	1,600	5,100	7.6	38
				75	12.9	286	2,000	5,700	6.9	42
				85	16.7	371	2,400	6,200	6.4	47
				100	23.3	517	3,000	6,900	5.7	57
	OPM-1182-059		22.2	50	8.0	178	1,500	3,900	8.5	37
				65	13.6	302	2,200	4,700	7.2	48
				75	18.1	402	2,600	5,100	6.5	58
				85	23.3	517	3,000	5,500	5.9	72
				100	31.5	699	3,600	6,000	5.2	HOT
	OPM-1202-066		14.8	50	6.1	90	1,000	2,600	11.2	31
				65	10.5	155	1,500	3,100	9.3	38
				75	14.2	210	1,800	3,500	8.5	44
				85	18.6	275	2,100	3,800	7.7	52
				100	25.1	371	2,600	4,100	6.9	66