

モーター負荷テストデータ

モーター	プロペラ	ESC	電圧 (V)	スロットル 開度 (%)	電流 (A)	消費電力 (W)	推力 (g)	回転数 (r.p.m.)	効率 (g/W)	表面温度 (°C)
OMM-4815-360	OPM-1162-053	OCM-3035	22.2	50	4.9	109	990	4,100	9.1	33
				65	8.4	186	1,500	5,000	8.0	37
				75	11.2	249	1,900	5,500	7.5	40
				85	14.5	322	2,200	6,000	6.8	44
				100	20.8	462	2,800	6,800	6.1	51
	OPM-1182-059		22.2	50	7.1	158	1,400	3,800	8.9	37
				65	12.3	273	2,100	4,600	7.5	47
				75	16.5	366	2,500	5,100	6.9	55
				85	21.5	477	3,000	5,500	6.3	65
				100	29.3	650	3,700	6,100	5.6	84
	OPM-1202-066		14.8	50	5.7	84	980	2,600	11.6	30
				65	9.9	147	1,500	3,100	10.0	36
				75	13.4	198	1,800	3,400	9.0	40
				85	17.4	258	2,100	3,700	8.2	46
				100	23.5	348	2,600	4,100	7.5	56
	OPM-1222-072		14.8	50	7.7	114	1,300	2,400	11.0	34
				65	12.8	189	1,800	2,800	9.4	44
				75	17.4	258	2,200	3,100	8.4	53
				85	21.9	324	2,500	3,400	7.7	62
				100	29.4	435	3,000	3,700	6.9	80