

モーター負荷テストデータ

モーター	プロペラ	ESC	電圧 (V)	スロットル 開度 (%)	電流 (A)	消費電力 (W)	推力 (g)	回転数 (r.p.m.)	効率 (g/W)	表面温度 (°C)
OMM-6015-330	OPM-1182-059	OCM-3075HV	22.2	50	7.1	158	1,400	3,800	9.1	32
				65	12.3	273	2,200	4,600	7.9	36
				75	17.3	384	2,800	5,200	7.2	38
				85	23.2	515	3,400	5,800	6.6	42
				100	33.8	750	4,400	6,500	5.8	50
	OPM-1202-066		22.2	50	10.2	226	2,000	3,600	8.9	34
				65	18.9	420	3,100	4,400	7.4	40
				75	24.5	544	3,800	4,800	6.9	45
				85	33.9	753	4,600	5,300	6.1	53
				100	47.3	1,050	5,700	5,900	5.4	71
	OPM-1222-072		14.8	50	7.3	108	1,300	2,400	11.9	28
				65	13.1	194	2,000	2,900	10.2	32
				75	18.3	271	2,500	3,300	9.3	35
				85	24.8	367	3,100	3,600	8.4	39
				100	35.2	521	3,900	4,100	7.4	46
	OPM-1242-079		14.8	50	9.7	144	1,600	2,300	11.4	31
				65	17.5	259	2,500	2,800	9.7	37
				75	24.0	355	3,100	3,100	8.7	43
				85	32.1	475	3,700	3,400	7.8	51
				100	44.5	659	4,500	3,700	6.9	66